



ISO-9001 Registered Quality System.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE Water Pump Lubricant

DESCRIPTION

LUBRIPLATE Water Pump Lubricant is a calcium based water-resistant grease designed specifically for water pump bearings found on vintage and classic cars.

APPLICATIONS & ADVANTAGES

LUBRIPLATE Water Pump Lubricant is an excellent lubricant for both plain and anti-friction bearings. This extremely water-resistant grease also provides excellent rust and corrosion protection.

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS
	ASTM	Water Pump Lubricant
Type of Base		Calcium
NLGI No.		2.5
Worked Penetration	D-217	235/260
Dropping Point	D-2265	190°F / 88°C
Viscosity:		
SUS @ 100°F	D-2161	300
cSt @ 40°C	D-445	58
Color	Visual	Off-White
Character		Smooth

PACKAGING AVAILABLE

Carton 12 – 16 oz. Tubs
35 lb. Pail
120 lb. Quarter Size Drum

Water Pump

L0038-004
L0038-035
L0038-039