

ISO-9001 Registered Quality System. ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE No. 105 & LUBRIPLATE C-AUTO 105

LUBRIPLATE No. 105 - THE MOTOR ASSEMBLY GREASE

DESCRIPTION

LUBRIPLATE No. 105 is a white, waterproof, NLGI No. 0, grease type lubricant possessing exceptional anti-seize properties and recommended extensively for coating all moving parts for motor assembly and rebuilding.

ADVANTAGES

LUBRIPLATE No. 105 has a multitude of other automotive, household and shop uses including:

- ⇒ Press Fittings
- ⇒ Striker Points
- ⇒ Battery Terminals
- ⇒ Windshield Wipers
- ⇒ Radio Antennas
- ⇒ Shackle Pin and Spring Assemblies
- ⇒ Wheel and Nut Assemblies
- ⇒ Hinges on Trunk and Hood
- ⇒ Anti-Seize Applications
- ⇒ General Rust Proofing of Parts and Tools
- ⇒ Remote Control Gear Shift Mechanisms
- ⇒ Manual Operated Steering Gear Mechanisms

APPLICATIONS

The suggested procedure is to apply LUBRIPLATE No. 105 as a light coating by means of a brush or swab or by spraying to all moving parts of the engine. This will include such applications as valve stems, pistons, rings, timing gears, main and rod bearings, and, in fact, every moving part of the internal combustion or diesel engine. This is to take place prior to assembly. This procedure will eliminate corrosion and seizure after the initial start.

It is a proven fact that when an engine is first started up, there is a short period before the oil in the crankcase can properly lubricate the entire working mechanism. During this period, high heats are developed and scoring of the moving parts take place. A thin film of LUBRIPLATE No. 105 has sufficient anti-seize properties to overcome this condition and, after the oil starts to circulate throughout the system, this light coating of LUBRIPLATE No. 105 dissipated into the oil with no deleterious results. Many motor rebuilders throughout the country, as well as manufacturers of original equipment, are following this procedure at the present time.

<u>LUBRIPLATE No. 105 is available in all standard size packages.</u> (See Tech Bulletin 3-13)

LUBRIPLATE No. 105 Motor Assembly Grease is available in the handy 10-ounce plastic tube, 36 tubes to a shipping case. Order as:

PACKAGING AVAILABLE P

Part No.

Case, 36/10 oz. Plastic Tubes

L0034-094

