

ISO-9001 Registered Quality System. ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE 989 SYNTHETIC COMPRESSOR LUBRICANT

DESCRIPTION

LUBRIPLATE 989 Synthetic Compressor Lubricant is a synthetic lubricant formulated for use in process gas compression applications that require wide operating temperature ranges and minimum interaction between the lubricant and the process gas.

APPLICATIONS

LUBRIPLATE 989 Synthetic Compressor Lubricant is intended for the lubrication of reciprocating compressors processing natural gas, carbon dioxide or other hydrocarbon gases. LUBRIPLATE 989 Synthetic Compressor Lubricant may also be used as a cylinder lubricant for natural gas, carbon dioxide and other gases that require chemical resistance in an ISO-150 viscosity grade.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS
Viscosity:		
cSt @ 40°C	ASTM D-445	138
cSt @ 100°C	ASTM D-445	24.4
Viscosity Index	ASTM D-2270	224
Pour Point °C	ASTM D-97	-42
Flash Point, COC, °C	ASTM D-92	245
Fire Point °C	ASTM D-92	270
Specific Gravity, 60°F	ASTM D-4052	1.052
Copper Strip Corrosion	ASTM D-130	1b

PACKAGING AVAILABLE

Part No.

55 Gallon Drum

L1010-062

