

ISO-9001 Registered Quality System. ISO-21469 Compliant.

Sales, Service & Distribution Center Newark, NJ 07105 Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center Toledo, OH 43605 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE CHAIN & CABLE HEAVY

DESCRIPTION

LUBRIPLATE Chain & Cable-Heavy is a lubricating, penetrating and cleaning lubricant designed for a multitude of heavy-duty applications. LUBRIPLATE Chain & Cable-Heavy will maintain a moist lubricating film that will not pick up dust and dirt but rather will act as a lubricating, cleansing and penetrating agent. In the lubrication of roller chains, it is most important not only to protect the surface of the chains, but also to penetrate and lubricate the inside of the links to provide total lubrication as well as prevention of rust and corrosion both on the inside and the outside.

APPLICATIONS

LUBRIPLATE Chain & Cable-Heavy is designed for medium and large size roller chains, heavy cables, drive chains on concrete mixers as well as other construction equipment and in all areas where an extreme pressure, heavy-duty, tacky, penetrating, lubricating and cleansing film is preferred.

ADVANTAGES

LUBRIPLATE Chain & Cable-Heavy has been used very successfully lubricating chains and slides under steamy wet conditions where other lubricants had failed miserably. Due to its clinging ability, LUBRIPLATE Chain & Cable-Heavy is also recommended for applications where a drip-less oil is required.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	716
Viscosity cSt @ 40°C	ASTM D-445	135
Viscosity SUS @ 210°F	ASTM D-2161	78
Viscosity cSt @ 100°C	ASTM D-445	15
ISO Grade	ASTM D-2422	150
SAE Grade		40
Flash Point	ASTM D-92	390°F/199°C
Fire Point	ASTM D-92	440°F/227°C
Pour Point	ASTM D-97	-10°F/-23°C
Color	ASTM D-1500	L-4.5
API Gravity	ASTM D-287	23.5

PACKAGING AVAILABLE

Part No.

L0136-007
L0136-013
L0136-035
L0136-039
L0136-040