



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE STO-4

DESCRIPTION

LUBRIPLATE STO-4 has excellent emulsifying properties to provide a lubricating film on the metal surfaces even in the presence of excessive moisture. LUBRIPLATE STO-4 is also compounded with detergent type additives to keep the metal surfaces from building up with undesirable residues.

APPLICATIONS

LUBRIPLATE STO-4 is a special compounded oil recommended for the lubrication of stirrups on bottle filling machines.

ADVANTAGES

- ⇒ Resists build-up and residue
- ⇒ Excellent lubrication even with excessive moisture



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	255
Viscosity cSt @ 40°C	ASTM D-445	45
ISO Grade		46
API Gravity	ASTM D-287	23.8
Color	ASTM D-1500	L-3.5
Flash Point	ASTM D-92	320°F/160°C
Fire Point	ASTM D-92	400°F/204°C
Pour Point	ASTM D-97	-30°F/-34°C

PACKAGING AVAILABLE

Part No.

5 Gallon Pail
55 Gallon Drum

L0860-060
L0860-062