

ISO-9001 Registered Quality System. ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support** 

Phone: 1-800-733-4755

### **PRODUCT DATA**

# **LUBRIPLATE SUPER GPO 30 MOTOR OIL**

## DESCRIPTION

LUBRIPLATE Super GPO 30 Motor Oil is premium quality engine oil for all-season use in commercial mixed-fleet engine operations. LUBRIPLATE Super GPO 30 Motor Oil is manufactured to meet the performance requirements in all naturally aspirated, turbocharged and supercharged diesel engines as well as all four-cycle gasoline engines.

#### Meets or exceeds the following specifications:

- ⇒ API CF-2
- ⇒ API CF
- ⇒ API CE (obsolete)
- ⇒ API CD-II (obsolete)
- ⇒ API CD
- ⇒ API SJ
- ⇒ API SH
- ⇒ MIL-L-2104F

# **APPLICATIONS**

LUBRIPLATE Super GPO 30 Motor Oil is recommended for all major automotive diesel and mixed fleet (diesel/four cycle gasoline engines) operations in all service and under all operating conditions where the equipment owner specifies the use of single grade engine oils.

#### **ADVANTAGES**

- ⇒ Resisted breakdown under high temperatures
- Maintained oil pressure under heavy load conditions
- Minimized rust and corrosion



# **Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	93
Viscosity cSt @ 100°C	ASTM D-445	11.8
SAE Grade		30
Viscosity Index	ASTM D-2270	>100
Sulfated Ash % wt	ASTM D-874	<1.0
Pour Point °F	ASTM D-5950	-27
TBN (min)	ASTM D-2896	7.5

PACKAGING AVAILABLE	Part No.
Carton, 12/1 Quart Plastic Bottles	L0749-054
5 Gallon Pail	L0749-060
55 Gallon Drum	L0749-062