



DURAGARD® 100% SYNTHETIC SAE 5W-30 MOTOR OIL



PREMIUM FORMULATION
Ultra Protection Ultra Performance Ultimate Wear Control



Duragard® dexos1® Approved Gen 2 100% Synthetic SAE 5W-30 Motor Oil meets or exceeds GM dexos1® Approved Gen 2 specifications for worldwide warranty requirements for all GM automotive gasoline engines currently in use. It is a fully synthetic formulation using the most advanced additive technology available to meet the latest fuel economy standards while exceeding the specifications for wear control, piston deposits, cleanliness, varnish and sludge, oxidation control, and emission system and seal compatibility. These specifications are far more stringent than ILSAC GF-6A specification.

Duragard® dexos1® Approved Gen 2 100% Synthetic SAE 5W-30 Motor Oil is an API SP and ILSAC GF-6A Resource Conserving Performance Motor Oil and is approved and licensed by General Motors for world wide warranty service for all GM gasoline engine cars and trucks where a SAE 5W-30 dexos1® Approved Gen 2 is required. Duragard® dexos1® Approved-Gen 2 100% Synthetic SAE 5W-30 supersedes the GM 6094M and GM 4718M specifications for current and older GM vehicles. Duragard® dexos1® is specifically designed for use in GM gasoline engines, but may be used wherever ILSAC GF-6A and API-SP or previous specifications are called for.

Customer Benefits with DIAMOND PLATE PROTECTION®

- * Meets or exceed GM dexos1™ Gen 2 specifications for worldwide warranty requirements for all GM automotive gasoline engines currently in use.
- * Engineered to improve fuel mileage and to maximize horsepower and acceleration and handle the most extreme conditions.
- * 100% pure synthetic oils for long lasting engine protection and performance.
- * Formulated for use in vehicles operating on ethanol-containing fuels up to E85.
- * Meets or exceeds API SP and ILSAC GF-6A requirements.

Product Code: DURDEXOS1-5W30

Product Containers Available:



Quart



2.5 gal.
2 pack



5 gal.



30 gal.



55 gal.



BULK



BULK
LIMITED AREA



Manufactured under license RB1A1104025 by **MAG1**

www.duragardoil.com

Made in USA with domestic and imported products.

2020 © Copyright ADVANTAGE DIST., LLC All Rights Reserved

Diamond Plate Protection®

DURAGARD® IS A REGISTERED TM OF ADVANTAGE DIST. LLC, ROCH., MN 55904

Rev 06/2020 PG-1



Application Specifications:

This product meets, or exceeds the requirements similar to the following manufacturers and global specifications:

API SP	Approved
dexos1® Gen2	Approved
ILSAC GF-6A	Approved
API SJ, SH, SG, SF	Meets Requirements
API SL	Meets Requirements
API SM	Meets Requirements
API SN	Meets Requirements
API SN Plus	Meets Requirements
Chrysler MS-6395	Meets Requirements
Ford WSS M2C946-B1, M2C946-A, M2C929-A	Meets Requirements
GM 4718M	Meets Requirements
GM 6094M	Meets Requirements
ILSAC GF-4	Meets Requirements

Typical Physical Specifications:

SAE GRADE 5W-30

Product Code: DURDEXOS1-5W30

INSPECTION INFORMATION	TEST METHOD	TYPICAL VALUE
Boron, wt. %	ASTM D5185	0.023
Calcium, wt. %	ASTM D5185	0.135
Cold Cranking Simulator at (°C), cP	ASTM D5293	4400 (-30)
Color	ASTM D1500	3
Flash Point °C	ASTM D92	227
Flash Point °F	ASTM D92	441
Foam Seq. III (Tendency/Stability), mL	ASTM D892 (Opt. A)	0/0
Foam Seq. II (Tendency/Stability), mL	ASTM D892 (Opt. A)	10/0
Foam Seq. I (Tendency/Stability), mL	ASTM D892 (Opt. A)	0/0
Gravity, °API	ASTM D287	35.82
High Temperature Foaming, static foam	ASTM D6082 (Opt A)	15/0
High Temperature / High Shear Vis at 100°C, cP	ASTM D6616	6.9
High Temperature / High Shear Vis at 150°C, cP	ASTM D5481	3.2
Magnesium, wt. %	ASTM D5185	0.059
Molybdenum, wt. %	ASTM D5185	0.0079
Nitrogen, wt. %	ASTM D4629	0.104

Typical test data average values only, minor variations which do not affect product performance are to be expected during normal manufacturing.



INSPECTION INFORMATION (CONT.)	TEST METHOD	TYPICAL VALUE
Noack Volatility, % loss	ASTM D6375	12
Phosphorus, wt. %	ASTM D5185	0.076
Pour Point °C (°F)	ASTM D5950	-45°C (-49°F)
Pumping Viscosity at (°C), cP	ASTM D4684	15,000 (-35)
Shear Stability, Final Viscosity in cSt	ASTM D6278	9.4
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8457
Sulfated Ash, wt. %	ASTM D874	0.9
Sulfur, wt. %	ASTM D4951	0.3
TBN, mgKOH/g	ASTM D2896	7.9
Viscosity @ 100°C cSt	ASTM D445	10.91
Viscosity @ 40°C cSt	ASTM D445	62.09
Viscosity Index	ASTM D2270	169
Zinc, wt. %	ASTM D5185	0.085

Typical test data average values only, minor variations which do not affect product performance are to be expected during normal manufacturing.

READ ENTIRE SDS BULLETIN FOR HANDLING AND SAFETY INFORMATION

READ ENTIRE SDS BULLETIN FOR HANDLING AND SAFETY INFORMATION

#1 In Customer Service And Technical Support

ADVANTAGE

Advantage Distributing and Lubricants, LLC

3434 Marion Rd SE
Rochester, MN 55904

1-800-420-1414 507-289-5555

INFO@ADVANTAGELUBES.COM