

SAFETY DATA SHEET

Vacuum Pump Oil; Vacuum Pump Oil Light

Section 1. Identification

GHS product identifier	: Vacuum Pump Oil; Vacuum Pump Oil Light
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Petroleum lubricating oil
Area of application	: Industrial applications.
Supplier/Manufacturer	: LUBRIPLATE® Lubricants Co. 129 Lockwood St. Newark, NJ 07105 Telephone no.: 1-973-589-9150
e-mail address of person	: SDS@lubriplate.com

responsible for this SDS	
Emergency telephone number (with hours of	: CHEM-TEL 1-800-255-3924 (24 hour)

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	: Not classified.
substance or mixture	
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: Avoid contact with skin and clothing. Wash thoroughly after handling.
Hazards not otherwise classified	: Prolonged or repeated contact may dry skin and cause irritation.

Date of issue/Date of revision

operation)

Section 3. Composition/information on ingredients

Substance/mixture Other means of identification

: Mixture

: Not available.

CAS number/other identifiers

CAS number	: Not applicable.
	· Not applicable.

Product code : Not available.

Ingredient name	Other names	%	CAS number
Distillates (petroleum), hydrotreated light paraffinic	Distillates (petroleum), hydrotreated light paraffinic	60-100	64742-55-8
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic	60-100	64742-54-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptom	oms/effects, acute and delayed
Potential acute health	<u>n effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Date of issue/Date of revision	
--------------------------------	--

Section 4. First aid measures

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

-	
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides nitrogen oxides phosphorus oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Date of issue/Date of revision

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8).	
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material in nandled, stored and processed. Workers should wash hands and face before e Irinking and smoking. Remove contaminated clothing and protective equipmer entering eating areas. See also Section 8 for additional information on hygiene neasures.	eating, nt before
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected lirect sunlight in a dry, cool and well-ventilated area, away from incompatible m see Section 10) and food and drink. Keep container tightly closed and sealed u eady for use. Containers that have been opened must be carefully resealed ar upright to prevent leakage. Do not store in unlabeled containers. Use appropria containment to avoid environmental contamination.	aterials until nd kept

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours.

Date of issue/Date of revision	: 04/30/2015	Date of previous issue	: No previous validation	Version	:1	4/11

Section 8. Exposure controls/personal protection

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measu	<u>'es</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid. [Oily liquid.]
Color	: Amber.
Odor	: Mineral oil.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Pour point: -37 to -21°C (-34.6 to -5.8°F)
Boiling point	: >288°C (>550.4°F)
Flash point	: Open cup: 219 to 252°C (426.2 to 485.6°F) [Cleveland.]
Evaporation rate	: <0.01 (butyl acetate = 1)
Flammability (solid, gas)	: Not applicable.
Lower and upper explosive (flammable) limits	: Lower: 0.9% Upper: 7%
Vapor pressure	: <0.0013 kPa (<0.01 mm Hg) [room temperature]
Vapor density	: >5 [Air = 1]
Date of issue/Date of revision	: 04/30/2015 Date of previous issue : No previous validation Version : 1 5/11

Section 9. Physical and chemical properties

Relative density: 0.87 to 0.88 [Water = 1]Solubility: Insoluble in the following materials: cold water and hot water.Solubility in water: Not available.Partition coefficient: n- octanol/water: Not available.Auto-ignition temperature: 227 to 277°C (440.6 to 530.6°F)Decomposition temperature: 227 to 277°C (440.6 to 530.6°F)Decomposition temperature: Not available.SADT: Not available.Viscosity: Not available.Physical/chemical properties comments: Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm²/s (6 to 12 cSt)			
Solubility in water: Not available.Partition coefficient: n- octanol/water: Not available.Auto-ignition temperature: 227 to 277°C (440.6 to 530.6°F)Decomposition temperature: Not available.SADT: Not available.Viscosity: Not available.Physical/chemical: Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt)	Relative density	:	0.87 to 0.88 [Water = 1]
Partition coefficient: n- octanol/water: Not available.Auto-ignition temperature: 227 to 277°C (440.6 to 530.6°F)Decomposition temperature: Not available.SADT: Not available.Viscosity: Not available.Physical/chemical: Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt): Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm²/s (6 to 12 cSt)	Solubility	:	Insoluble in the following materials: cold water and hot water.
octanol/waterAuto-ignition temperature:227 to 277°C (440.6 to 530.6°F)Decomposition temperature:Not available.SADT:Viscosity:Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt):Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm²/s (6 to 12 cSt)	Solubility in water	:	Not available.
Decomposition temperature: Not available.SADT: Not available.Viscosity: Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt)Physical/chemical: Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm²/s (6 to 12 cSt)		:	Not available.
SADT : Not available. Viscosity : Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt) Physical/chemical : Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm²/s (6 to 12 cSt)	Auto-ignition temperature	:	227 to 277°C (440.6 to 530.6°F)
Viscosity : Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt) Physical/chemical : Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm²/s (6 to 12 cSt)	Decomposition temperature	:	Not available.
Physical/chemical : Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm ² /s (6 to 12 cSt)	SADT	:	Not available.
•	Viscosity	:	Kinematic (40°C (104°F)): 0.34 to 0.97 cm²/s (34 to 97 cSt)
	-	:	Kinematic viscosity (100°C (212°F)): 0.06 to 0.12 cm ² /s (6 to 12 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
	Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: Keep away from heat, sparks and flame.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials. Chlorine
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects **Acute toxicity** Not available. **Irritation/Corrosion** Not available. **Sensitization** Not available. **Mutagenicity** Not available. **Carcinogenicity** Not available. **Conclusion/Summary**

: The mineral oils in the product contain < 3% DMSO extract (IP 346).

Reproductive toxicity

Date of issue/Date of revision

:04/30/2015 Date of previous issue

Section 11. Toxicological information

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard			
Name		Result	
Distillates (petroleum), hydro Distillates (petroleum), hydro		ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1	
Information on the likely routes of exposure	: Routes of entry anticipated: Ora	al, Dermal, Inhalation.	
Potential acute health effects	<u>s</u>		
Eye contact	: No known significant effects or	critical hazards.	
Inhalation	: No known significant effects or	critical hazards.	
Skin contact	: Defatting to the skin. May caus	e skin dryness and irritation.	
Ingestion	: No known significant effects or	critical hazards.	
Symptoms related to the phy	vsical, chemical and toxicological	<u>characteristics</u>	
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include irritation dryness cracking	e the following:	
Ingestion	: No specific data.		
<u>Delayed and immediate effec</u> <u>Short term exposure</u> Potential immediate	cts and also chronic effects from s	short and long term exposure	
effects			
Potential delayed effects	: Not available.		
Long term exposure Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health eff Not available.			
General	: Prolonged or repeated contact of dermatitis.	can defat the skin and lead to irritation, cracking and/or	
Carcinogenicity	: No known significant effects or	critical hazards.	
L			

: 04/30/2015 Date of previous issue

Version :1

: No previous validation

7/11

Date of issue/Date of revision

Section 11. Toxicological information

Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), hydrotreated light paraffinic	>2	-	low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

8/11

Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) PAIR: diphenylamine						
	United States inventory (TSCA 8b): All components are listed or exempted.						
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed						
Clean Air Act Section 602 Class I Substances	: Not listed						
Clean Air Act Section 602 Class II Substances	: Not listed						
DEA List I Chemicals (Precursor Chemicals)	: Not listed						
DEA List II Chemicals (Essential Chemicals)	: Not listed						
SARA 302/304							
Composition/information of	on ingredients						
No products were found.							
SARA 304 RQ	: Not applicable.						
SARA 311/312							
Classification	: Immediate (acute) health hazard						
Date of issue/Date of revision	: 04/30/2015 Date of previous issue : No previous validation Version : 1 9/11						

Section 15. Regulatory information

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), hydrotreated	60-100 60-100	No. No.	No. No.	No. No.	Yes. Yes.	No. No.
0	60-100	No.	No.	No.	Yes.	

SARA 313

Not applicable.

State regulations

Massachusetts	 The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC
New York	: None of the components are listed.
New Jersey	: The following components are listed: MINERAL OIL (HIGHLY REFINED); OIL MIST, MINERAL; MINERAL OIL (HIGHLY REFINED); OIL MIST, MINERAL
Pennsylvania	: None of the components are listed.
California Prop. 65	

None of the components are listed.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>History</u>	
Date of issue/Date of revision	: 04/30/2015
Date of previous issue	: No previous validation
Version	: 1
Prepared by	: IHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	: HCS (U.S.A.)- Hazard Communication Standard International transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.